



CAPILLARY COPPER TUBING

Copper tubing is most often used for heating systems and as a [refrigerant](#) line in [HVAC](#) systems. Since copper is durable and corrosion resistant it can also withstand high temperatures — this is why it was so popular for the transportation of hot and cold water. Copper is recyclable, meaning you can reduce your environmental impact by using it.



SKU: N/A

Categories: [Copper](#), [Tubing & Pipes](#)

PRODUCT DESCRIPTION

Alloys:

C122 - Deoxidized High Phosphorus (DHP) Copper

Specifications:

ASTM B280 / ASME SB280

OD Range: 0.047" to 0.090"



Wall Thickness: 0.023" -> 0.090"

Length: Per Request

Tempers:

Hard

Annealed

Types: Available in cut lengths, coil or straight lengths

Industries:

Automotive

Electrical components

Machining

Refrigeration

Temperature controls

Process equipment



ADDITIONAL INFORMATION

OD Range	0.250" -> 4.00"
Wall Thickness	0.020" -> 0.083"
Length	Per Request
Tempers	061 (Annealed), H80 (Hard Drawn), H55 (Light Drawn)
Types	Available in coil or straight lengths
Industries	Automotive, Electrical components, Machining, Refrigeration, Plumbing, Heat exchanger